







1/4 TURN ASC ACTUATORS



1/4 TURN ASC ACTUATORS

CHARACTERISTICS

- ✓ Single acting Fail Safe closing or opening: torque until 1000N.m at 5.5 barg
- ✓ Double acting: torque until 1000N.m at 5.5 barg
- ✓ Fluid media: air
- ✓ Rotation: 0 to 90°
- ✓ Temperature of use: -20°C to +80°C (on demand: + 140°C)

SUPPLY PRESSURE

✓ 2.5 barg at 10 barg depending on models.

STANDARD DESIGN

- ✓ Ductile Iron housing
- Carbon steel cylinder with Epoxy PTFE coating (others on demand)
- ✓ Carbon steel alloy output shaft
- ✓ Scotch-yoke design
- ✓ Carbon steel flanges
- ✓ Position indicator
- ✓ Connections: 1/4" to 1/2" as standard (others on demand)
- ✓ Topwork acc. to ISO 5211

OPTIONS

- ✓ Control systems
- ✓ Manual override
- ✓ Safety tank
- ✓ Fast strokes (under 1s)
- ✓ SS 316 or cast iron housing
- ✓ Fire Proofing
- Special studies acc. to your request.

TOTAL EP / EGINA





TOTAL EP / KAOMBO



